

Data Description

The document introduces the data of feature matrices and noise tensor used in paper [1] and [2]. Please cite the following two papers when using the datasets.

- [1] Yu Zheng, Tong Liu, Yilun Wang, Yanchi Liu, Yanmin Zhu, Eric Chang. [Diagnosing New York City's Noises with Ubiquitous Data](#). In Proceedings of UbiComp 2014.
 [2] Wang, Y., Zheng, Y., Liu, T. [A noise map of New York City](#). In Proc. of UbiComp 2014.

There are four data sources we use for diagnosing NYC's noises: 311 data about noise, user check-in data, road networks and POIs. First, we have segmented NYC map into 1199 disjointed regions according to its major roads. Each region is a basic geographic unit to study noises and features.

We modeled the noises using a tensor \mathcal{A} with three dimensions denoting regions, noise categories and time slots, respectively. According to the 311 data, we extracted 14 noise categories. We divided a day into 24 equal time slots, one hour for each time slot. Therefore, there is $\mathcal{A} \in \mathbb{R}^{1199 \times 14 \times 24}$. An entry $\mathcal{A}(i, j, k)$ stores the total number of 311 complaints of category c_j in region r_i and time slot t_k over the given period of time (e.g., 168 weekdays or 68 weekends). A tensor is stored in **A.mat**.




Figure 1. Tensor and feature matrices




Figure 2. 311 complaints of a location

To deal with the data sparsity problem, we extract three categories of features: geographical features, the noise category correlation features, and human mobility features (denoted by matrices B , C , and D , as shown in Figure 1).

The geographical feature $B \in \mathbb{R}^{1199 \times 22}$, is comprised of two parts: POI features and road network features. POI features, in the first 15 columns of B , are extracted from POIs falling in a region, consisting of the total number of POIs over 15 categories: *Entertainment & Arts*, *Vehicles*, *Business to Business*, *Computers*, *Education*, *Food & Dining*, *Government*, *Health & Beauty*, *Home & Family*, *Legal & Finance*, *Professional & Services*, *Estate & Construction*, *Shopping*, *Sports & Recreation*, and *Travel*. Road network features consist of the number of intersections and the total length of road segments in different levels ($\in [1, 6]$), which are in the last 7 columns of B . Matrix B is stored in **B.mat**.

The correlation between different noise categories $C \in \mathbb{R}^{14 \times 14}$ can be learned from the 311 data itself. The complaints within a circle distance of 100 meters to a location is counted for the location, as shown in Figure 2. For each complaint of a noise category, we counted the number of complaints of each other category around it and summed together. An entry c_{ij} represents the total number of noise complaints in category j around noise complaints in category i . Matrix C is stored in **C.mat**.

Human mobility features $D \in \mathbb{R}^{1199 \times 24}$ are derived from check-ins created by users in different regions and time slots. An entry d_{ki} of matrix D denotes the number of check-ins generated in region r_i and time slot t_k . Matrix D is stored in **D.mat**.

As weekdays and weekends have different noise patterns and features, we built a tensor and feature matrices for them separately. Each of file folders *weekday* and *weekend* encloses a tensor *A.mat* and three features *B.mat*, *C.mat* and *D.mat*.

Contact:

Dr. Yu Zheng, yuzheng@microsoft.com

Lead Researcher at Microsoft Research

<http://research.microsoft.com/en-us/people/yuzheng/>